

QuickSwitch® 6272 ST Duplex Fiber Optic Mirror A/B Switch with Remote Serial Control

INTRODUCTION

The QuickSwitch® 6272 ST Duplex Fiber Optic A/B Switch with Remote Serial Control provides a powerful and versatile tool to manage switching requirements. The system affords local and remote access functionality. Remote access can be accomplished by RS232 commands sent via the Remote Serial Port. Users can remotely monitor status and control switch functions.



FEATURES:

- The switch uses mirror technology and is transparent to data and speed.
- A/B/COM Ports are ST Duplex, MultiMode 62.5/125 Micron.
- The switch supports Fiber Optic wavelength of 1300 nm and gigabyte data rate.
- Front panel pushbutton control or Remote ASCII Command access through the serial port.
- Front panel LED's display the current switch position.
- DB9/Female RS232 Serial Port for remote control.
- Switching time less than 1 msec.
- Rackmount configuration is standard.

SPECIFICATIONS:

WAVELENGTH: 1300 nm.
 PORT CONNECTORS: (3) ST duplex fiber optic rear panel connectors, labeled A, B, COMMON.
 CONTROL: Front panel pushbutton allows local selection of switch position.
 REMOTE CONTROL: (1) DB9 (F) connector on rear panel accepts serial RS232.
 DISPLAY: (2) Red LED's display switch position, status, and power presence.
 POWER: UL Approved 120 VAC, 60 Hz wall mount power module supplies 12 VAC, 500 mA to the Model 6272.
 DIMENSIONS: 19.0" W x 1.75" H x 8.0" D.
 WEIGHT: Approximately 4.5 lbs

