



Fittings and Accessories

Compressed Air Hose Connectors and Clamps

Barbed Fitting - Female Type C-...



SW = wrench size (mm)

Order Number		I.D. in / mm	Thread D	Orifice Size in / mm	Material	Weight lb / kg	Dimensions	
Part No.	Type						L in / mm	SW mm
2021	C-1/8-P-6	0.24 / 6	G 1/8 ISO	0.16 / 4	Brass	0.040 / 0.018	1.42 / 36	13
2022	C-1/4-P-6	0.24 / 6	G 1/4 ISO	0.18 / 4.5		0.062 / 0.028	1.53 / 39	17
2023	C-1/4-P-9	0.35 / 9	G 1/4 ISO	0.22 / 5.5		0.075 / 0.034	1.53 / 39	17
2024	C-3/8-P-6	0.24 / 6	G 3/8 ISO	0.18 / 4.5		0.068 / 0.031	1.53 / 39	19
2025	C-3/8-P-9	0.35 / 9	G 3/8 ISO	0.26 / 6.5		0.075 / 0.034	1.53 / 39	19
2026	C-1/2-P-13	0.51 / 13	G 1/2 ISO	0.43 / 11		0.141 / 0.064	1.97 / 50	24

Hose Clamps Type SK-... per DIN 3017

The hose clamps are adjusted with a worm screw. Width of the clamps is 0.32 in / 8 mm.



Order Number		Clamp Diameter Range in / mm	Material	Weight lb / kg
Part No.	Type			
9274	SK-10-16	0.4 to 0.6 / 10 to 16	Steel	0.015 / 0.007
9275	SK-16-25	0.6 to 1.0 / 16 to 25		0.026 / 0.012
9276	SK-20-32	0.8 to 1.3 / 20 to 32		0.029 / 0.013