


785'392'3017 FAX 785.392.2845

REVISED 09-02





CL DD4	Nominal	Length	WEIGHT	MATERIALS		Use With
CLPM		(L)	Kg. per 100 Pieces	Plain "CLPM-"	Zinc Clear "CLPMZ-"	
	DIAMETER	LENGTH		CLPIVI-	CLPINIZ-	
-040-012	4	12	0.10			CPMZ-010-008
-050-015	5	15	0.30			CPMZ-016-008
-060-018	6	18	0.40			CPMZ-016-010
-080-023	8	23	0.90			CPMZ-020-012
-100-029	10	29	1.70			CPMZ-032-016
-120-035	12	35	3.00			CPMZ-040-020
-140-040	14	40	4.80			CPMZ-040-025
-160-045	16	45	6.70			CPMZ-040-025
-200-053	20	53	12.50			CPMZ-050-028
-250-067	25	67	26.00			CPMZ-063-032

DIN 1434 Solid pin with standard flat head that secures with a wire form pin through a hole drilled in the opposite end. Clevis pins are used as a quick and secure fastener for various applications.

DESCRIPTION



GENERAL USE

1. Verify flat head pin with hole at opposite end.

- 2. Measure diameter (D).
- 3. Measure length (L).
- 4. Find the part in the chart above.

TYPICAL PART NUMBER SEQUENCE: CLPM-060-018

HOW TO IDENTIFY

is a 6mm x 18mm plain clevis pin.


Secured with a ring cotter pin.

CORNPICKER

PERFORMANCE RESULTS VARY. YOUR PIN SELECTION SHOULD BE MADE BASED ON INDIVIDUAL APPLICATION.







	LYNGH						'
	MANUFACTURER CROSS-REFERENCE						
	Bossa	ard	BN 914		DIN	11023	
LPM			Nominal (D)		Length (L)		WEIGH
							Kg. pe

I DRA	Nominal	Length	WEIGHT Kg. per	MATERIAL
LPM	(D)	(L)	100	Zinc Clear
	DIAMETER	LENGTH	Pieces	"LPM-"
-040-027	4	27	0.86	
-045-032	4.5	32	2.12	
-060-040	6	40	2.72	
-070-040	7	40	3.18	
-080-045	8	45	4.08	
-090-045	9	45	4.31	
-100-045	10	45	4.76	
-110-045	11	45	5.67	



