

SMN - FLOW SWITCH FOR LIQUIDS



Flow
Pressure
Level
Temperature
measurement
monitoring
control

S2



- Low Switch Point
- Low Pressure Drop at High Flows
- Adjustable Reed Contact
- Brass or SS Construction
- Maximum Pressure: 5000 PSIG
- Maximum Temperature: 250°F



USA

KOBOLD Instruments Inc.
1801 Parkway View Drive
USA-Pittsburgh, PA 15205
☎ +1 412-788-2830
Fax +1 412-788-4890
E-mail: info@koboldusa.com



CANADA

KOBOLD Instruments Canada Inc.
9A Aviation
Pointe-Claire, QC H9R 4Z2
☎ +1 514-428-8090
Fax +1 514-428-8899
E-mail: kobold@kobold.ca


Visit KOBOLD Online at
www.kobold.com

Model:
SMN



Special Features


- Low Switch Point
- Low Pressure Drop at High Flows
- Adjustable Reed Contact
- Brass or SS Construction
- Maximum Pressure: 5000 PSIG
- Maximum Temperature: 250°F



KOBOLD SMN flow switches are used when extremely low flow switching points are required in combination with minimum pressure loss at high flow rates. Typical applications include the control of water and cooling circuits, high pressure cleaning devices, control of contaminated media in effluent and heating systems and a wide variety of other flow control systems.

The KOBOLD SMN, with all-metal wetted parts, works on the float principle. However, it does not use the standard conical metering tube or slotted measuring nozzle. Instead, a float with an integral magnet is suspended within a cylindrical measuring tube. The float is moved by the flow stream against the magnetic field of an opposing magnet mounted in the top of the instrument. The magnetic field produced by the float activates a reed contact at the switch point. The reed contact is mounted on the outside of the SMN body.

The special construction of the SMN float and flow tube means that only a low flow is required to raise the float and thus close the contact. When the float reaches the top of its travel, an additional flow path opens, allowing high flow rates without a significant



increase in pressure loss. When the flow is interrupted, the float is moved back down the flow tube by the opposing magnetic field and the contact opens.

Specifications

- Switching Range:**
on: 0.4-13 GPM H₂O
off: 0.25-1 GPM H₂O
- Housing Material:** Brass or SS
Max. Temperature: 250°F
Maximum Pressure:
Brass: 3600 PSIG
SS: 5000 PSIG
Fittings: 1" NPT
Contact: N/O or SPDT
Maximum Contact Ratings:
N/O: 240 VAC, 100 VA, 1.5 A
SPDT: 240 VAC, 60 VA, 1 A
Protection: NEMA 4
Approvals: UL, CSA

Order Numbers	
Material	Model
Brass	SMN-5150
SS	SMN-5250
Options (add suffix to Order Number)	
Suffix	
"U"	SPDT Contact

Subject to change without prior notice.