




Model
IR2

Infrared Non-Contact Thermometer

12:1 Distance-to-Target Ratio, Laser Sighting



The **Model IR2 Infrared Temperature Thermometer** allows users to economically take accurate measurements in hard to reach areas. Measurements can be taken at a safe distance with a 12:1 Distance to Target Ratio. The IR2 easily takes measurements within 2% accuracy using a built-in laser sighting. The fixed emissivity of 0.95 is perfect for measuring surface temperatures of concrete, asphalt, rubber or oxidized metals. Besides reading the process temperature, the back lit display also reads the maximum temperature seen. Excellent for monitoring surface temperatures of air ducts, boilers, engines or light fixtures.

Model IR2, Infrared Temperature Thermometer

SPECIFICATIONS

Measurement Range: -76 to 932°F (-60 to 500°C).

Operating Range: 32 to 122°F (0 to 50°C).

Accuracy: 2% of reading or 4°F (2°C), whichever is greater.

Resolution: 0.1°F/0.1°C.

Response Time: 1 second.

Distance to Target: 12:1.

Emissivity: 0.95 fixed.

Battery Life: 2 AAA, 180 hours continuous use (auto power off after 15 seconds).

Weight: 3.61 oz (102 g).

Agency Approvals: CE.