

490

## Wet/Wet Handheld Digital Manometer Liquid & Gas Pressure Measurement, ±0.5% F.S. Accuracy

**SPECIFICATIONS** 



Series 490 Digital Manometers are versatile, hand-held, battery operated manometers available in several basic ranges for positive or positive differential pressure measurement and can tolerate most liquid media compatible with 316LSS.

A memory function allows storage of up to 40 readings for later recall and a backlight provides auxiliary lighting for hard-to-see locations.

Standard are a hold feature and both visual and audible overpressure alarms. A new feature added to the Series 490 is a field adjustable damping. This allows the user to choose the level of display averaging rate corresponding to the fluctuation level common in many applications. A 9V alkaline battery is included that provides up to 100 hours of operation.

Service: Compatible gases & liquids. Wetted Materials: Type 316L SS.

Accuracy: ±0.5% F.S., 60 to 78°F (15.6 to 25.6°C); ±1.5% F.S. from 32 to 60°F and 78 to

104°F (0 to 15.6°C and 25.6 to 40°C). Pressure Hysteresis: ±0.1% of full scale.

Pressure Limits: See chart.

Temperature Limits: 32 to 104°F (0 to 40°C).

Storage Temperature Limits: -4 to 176°F (-20 to 80°C).

**Display:** 0.42" (10.6 mm) 4 digit LCD.

Resolution: See chart.

Power Requirements: 9 volt alkaline battery. Battery included but not connected.

Weight: 14.1 oz (400 g).

Connections: Two 1/8" (3.18 mm) female NPT.

Agency Approvals: CE.

|       |             |       |       |       |       |       |       |      |      | Maximum   |
|-------|-------------|-------|-------|-------|-------|-------|-------|------|------|-----------|
|       |             |       |       |       |       |       |       |      |      | Pressure  |
| 490-1 | 0-15.00 psi | 1.034 | 15.00 | 30.54 | 103.4 | 34.60 | 415.2 |      |      |           |
| 490-2 | 0-30.00 psi | 2.069 | 30.00 | 61.08 | 206.9 | 69.20 | 830.4 |      |      | 60 psig   |
| 490-3 | 0-50.00 psi | 3.447 | 50.00 | 101.8 | 344.7 | 115.3 | 1384  | 2585 | 3447 | 100 psig  |
| 490-4 | 0-100.0 psi | 6.895 | 100.0 | 203.6 | 689.5 | 230.7 | 2768  | 5171 | 6895 | 200 psig  |
| 490-5 | 0-500.0 psi | 34.47 | 500.0 | 1018  | 3447  | 1153  |       |      |      | 1000 psig |
| 490-6 | 0-200.0 psi | 13.79 | 200.0 | 407.2 | 1379  | 461.3 | 5536  |      |      | 400 psig  |



-3V, 3-way Valve Package

Note: Option only available on ranges up to 100 psi.



**A-402A Carrying Case** — Tough gray nylon pouch protects any Series 490 Wet/Wet Handheld Digital Manometer. Double zippered for guick and easy access. With belt loop that snaps closed. 7-1/2"H x 3"W x 2-1/4"D (191 x 76 x 57 mm)

