









SpiralVeyor SVX-DL Dual Lane




- Continuous elevator / buffer system
- Two or more parallel product flows
- Designed for high capacity dual lane packing lines
- **Space-saving design**
- Patented design















SpiralVeyor SVX-DL

The SpiralVeyor® SVX DL-series (Dual Lane) is designed to elevate packed items like boxes, six packs, bundles and wrapped bottle packs. Technology wise comparable with the popular SpiralVeyor® SV the SVX (X stands for Extended) is fitted with more belt lanes to accommodate different product flows in one machine.

This unique feature allows multiple product lines to elevate side by side, ideally catering to modern packaging lanes which produce in dual lanes. Each line speed can be controlled separately and even run in opposite directions.

General features:

The general and distinctive feature match those of the SpiralVeyor® SV.















- The belt width ranges from 200 600 mm per belt.
- Two or three belts running parallel.
- Belt speed up to 90 m/min.
- Loads up to 50 kg/m per lane.
- Angle of incline up to 15 degrees.

Material configurations:

- **S** Mild steel, coated.
- **CR** High Corrosion resistant coated mild steel frame, stainless parts and a special CR-chain.
- RS Stainless steel frame and moving parts (wash down / wet environment).

Alternative machines:

- SpiralVeyor® SV Similar but with one lane
- SpiralVeyor® SVX EB-series (Extended Belt). Similar machine where parallel belts are used as one belt to accommodate oversized products.
- SpiralVeyor® SVM has multiple 100 mm chaine arrangements, up to 500 mm wide, to handle individual products like cans and bottles.

SpiralVeyor®	Belt configuration	Foot print
SVX-2/200	2 X 200 mm	1.720 mm square
SVX-3/200	3 X 200 mm	2.200 mm square
SVX-2/400	2 X 400 mm	2.620 mm square
SVX-200/600	1 X 200, 1 X 600 mm	2.520 mm square
Other combinations: 200, 400, 600 mm		

More info:

www.spiralveyor.com



Office EUROPE, Holland Office NORTH AMERICA. USA Office ASIA. Singapore

mail@ambaflex.com info@ambaflex.com info singapore@ambaflex.com phone +31 (0)229 285 130 phone (877) 800 1634 phone (65) 6560 2866

fax +31 (0)229 285 131 fax (877) 800 1635 fax (65) 6554 2868