

PathWay® Model 7200 DB-9 A/B Switch, with Remote Control, Desktop

INTRODUCTION:

The PathWay® Model 7200 DB-9 A/B Switch with Remote Control allows the user the capability of accessing two separate devices, ports A & B, via connection through a device connected to the Common port of the switch.

The switch may be controlled manually via the front panel pushbutton or remotely from an RS232 serial port located on the rear of the unit.

Switch position state may be attained via the front panel LED display or the remote RS232 serial port (DB9) located on the rear of the unit.

FEATURES:

- A, B, and COMMON connectors are DB9.
- All 9 interface pins are switched.
- The switch ports are transparent to all data.
- Front panel pushbutton control or Remote ASCII RS232 Serial Data Control via the serial port.
- Front panel LEDs display the switch position and power status.
- Front panel pushbutton control can be locked out remotely.
- The unit maintains last set position on power loss and continues to pass data.

OPTION: WIDE RANGE POWER MODULE

(Cat No 517277) 100VAC/240VAC, 50Hz/60Hz in place of standard 115VAC or 120VAC power module. Ideal for international applications.



SPECIFICATIONS:

PORT CONNECTORS: (3) DB9 (F) connectors labeled A, B, and COMMON.

FRONT PANEL CONTROL: (1) Manual pushbutton allows local switching.

DISPLAY: (2) Front panel LED's display switch position and power status.

REMOTE CONTROL: (1) DB9 Female connector on rear panel accepts ASCII RS232 Serial Data for remote control operation.

POWER: UL approved 120 VAC, 60 Hz wall mount power module supplies 12 VDC, 500mA to the unit. An international wide range power module is available as an option.

DIMENSIONS: Desktop, 7.75" W x 7.0" D x 2.75" H.

WEIGHT: Approximately 2.8 lbs

APPLICATION: Model 7200

