

PathWay® Model 7202 BNC A/B Switch with RS232 Serial Remote Port

- **Ideal for sharing laboratory test equipment having a BNC coaxial cable interface.**

INTRODUCTION

The PathWay® Model 7202 BNC A/B Switch with Remote allows the user the capability of accessing two separate BNC ports via the COMMON port. The switch may be controlled manually via a front panel pushbutton or remotely from a DB9/female RS232 serial port located on the rear of the unit. Switch position status may be attained via the front panel LED display or the remote RS232 serial port located on the rear of the unit.

FEATURES:

- Allows quick connection to any one of two BNC interface devices from one COMMON device.
- (3) Isolated BNC connectors on rear panel.
- Center pin and shell of each BNC connector is switched.
- Eliminates the need to plug and unplug cables.
- Local control via front-panel pushbutton.
- The REMOTE port accepts RS232 Serial Data ASCII commands for switch position and control.
- Front panel LED's display switch position and power status.
- Retains last switch position in the event of a power loss and continues to pass data.
- Attractive anodized black box packaging provides EMI/RFI shielding.
- Custom length BNC coaxial cables available for your switch installation.

- ★ **Municipalities, schools, government: This product on GSA Schedule!**



SPECIFICATIONS:

PORT CONNECTORS: (3) BNC (F) connectors labeled A, B and COMMON.

FRONT PANEL CONTROL: (1) Manual pushbutton allows local switching.

DISPLAY: (2) Front panel LED's display switch position and power status.

REMOTE CONTROL: (1) DB9(F) REMOTE connector on rear panel accepts ASCII RS232 Serial Data.

POWER: UL approved 120 VAC, 60 Hz wall mount power module supplies 12 VDC, 500mA to the unit.

DIMENSIONS: Desktop 5.25" W x 7.25" D x 2.0" H. (13.3 x 18.4 x 5.1 cm)

WEIGHT: Approximately 2.0 lbs. (0.91 Kg)

OPTION: WIDE RANGE POWER MODULE

(Cat No 517277) CE and UL listed table mount power module, 100VAC/240VAC, 50Hz/60Hz in place of standard 115VAC or 120VAC power module. Ideal for international applications.

MODEL 7202 APPLICATION: Sharing Laboratory Test Equipment

