

PathWay® Model 7207 DB9 A/B/C/D Switch with Exclusive Remote Control, Desktop

INTRODUCTION

The PathWay® Model 7207 DB9 Interface A/B/C/D Switch provides switching in a compact, desktop unit. It allows the user the capability of sharing a single DB9 interface device connected to the Common port among four other devices connected to the "A", "B", "C", and "D" ports.

There is no "local" or front panel switch control on the unit. The Model 7207 can ONLY be switched remotely from the DB9/female RS-232 serial interface remote port located on the rear of the unit. The front panel LED display indicates the switch position and unit power status.

FEATURES:

- The switch ports are transparent to data format.
 - All nine (9) pins of the DB9 interface are switched.
 - The REMOTE port accepts RS232 Serial data ASCII commands for switch position control and monitoring.
 - The unit maintains last set switch position in the event of a power loss and continues to pass data.
 - Front panel LEDs display the current switch position and power status.
 - Desktop configuration is standard.
- **Ideal for "remote control only" applications. There is no local control on the Model 7207.**

OPTION: WIDE RANGE POWER MODULE

(Cat No 517277) CE and UL listed wall mount power module, 100VAC/240VAC, 50Hz/60Hz in place of standard 115VAC or 120VAC power module. Ideal for international applications.



SPECIFICATIONS:

PORT CONNECTORS: (5) DB9(F) connectors labeled A, B, C, D and COMMON.

REMOTE CONTROL: (1) DB9(F) connector labeled REMOTE accepts RS232 serial data ASCII commands.

DISPLAY: (4) LED's labeled A, B, C and D display switch position.
(1) LED labeled POWER displays power position.

POWER: UL approved 120VAC, 60Hz wall mount power module supplies 12 VDC, 500 mA to the unit.

DIMENSIONS: Desktop configuration 2.4" H x 8.0" W x 7.25" D.

WEIGHT: Approximately 4.5 lbs

Custom Length DB9 cables available!

MODEL 7207 APPLICATION:

