

## **PathWay® Model 7269V DB9 Interface A/B Switch Configured to Support Tandberg Camera/Codec Connections, with Serial Remote Control Port**

- **Ideal for switching Video Conferencing, Broadcast, and Presentation Systems.**

### INTRODUCTION

The PathWay® Model 7269V DB9 Interface A/B Switch allows the user the capability of sharing a single DB9 interface device connected to the Common port among two other devices connected to the "A" and "B" ports. The "A", "B", and "COM" ports are configured to support Tandberg Camera/Codec video conferencing connections.

The switch may be controlled locally by manually operating the front panel pushbutton or remotely from the DB9/female serial interface Control port located on the rear of the unit. Switch position states may be attained locally via the front panel LED display or remotely using RS232 serial data commands.

### FEATURES:

- The switch ports are transparent to all data.
- All pins of the DB9 interface are switched.
- **Pins 1 and 6 use Cat6 cable material.**
- **Pins 4 and 5 support 12VDC, 1.5A.**
- All other pins support serial data communications.
- Local position control using the front panel pushbutton.
- Serial Remote Control to switch the position of the Model 7269V, lock and unlock the front panel, and query its status.
- The Model 7269V maintains position and continues to pass data during power loss.
- Front panel LED's display the current switch position and the switch power status.

### WIDE RANGE POWER OPTION AVAILABLE:

(Cat No 517277) CE and UL listed table mount power module, 100VAC/240VAC, 50Hz/60Hz in place of standard 115VAC or 120VAC power module. Ideal for international applications.



### SPECIFICATIONS:

**PORT CONNECTORS:** (3) DB9 female connectors labeled A, B, and COMMON.

**FRONT PANEL CONTROL:** (1) Manual pushbutton allows local switching.

**DISPLAY:** (2) Front panel LED's display switch position and power status.

**REMOTE:** (1) DB9 female connector on rear panel accepts ASCII RS232 Serial Data for Remote Control operation.

**POWER:** UL approved 120VAC, 60 Hz wall mount power module supplies 12 VDC, 500mA to the unit.

**DIMENSIONS:** Rackmount configuration 19.0" W x 1.75." H x 8.0" D. (48.3 x 4.4 x 20.3 cm)

**WEIGHT:** Approximately 4.5 lbs. (2.0 kg)

**Custom Length  
cables available.  
Quick Delivery!**

### Model 7269V Application

