

Model 7273 DB25 A/B Switch with Serial Remote Control Port

- Remote port provides switch control based on an ASCII character command set.

The Model 7273 Single Channel DB25 A/B Switch allows the user the capability of sharing a DB25 device connected to the Common port connector between two other devices connected to the "A" and "B" ports. The switch may be controlled locally by a pushbutton located on the front panel. The switch may be controlled remotely as well from the serial Remote port located on the rear panel of the unit. The front panel LED display indicates the switch position and unit power status.



Model 7273 Features:

- Ideal for sharing or fallback applications.
- Serial Remote Port located on the rear panel.
- All (25) signals of the DB25 connector interface are switched.
- Transparent to data speed and protocol.
- Switch retains the current switch position in the event of a power failure.
- Front panel LED's indicate switch position and power status.
- Manual control via the front panel pushbutton.
- Remote control from the DB9 Remote port on the rear panel.
- Remote control based on ASCII character set.

Specifications

Model:7273

Connectors: (3) DB25/female connectors, A, B & COM.
(1) DB9/female, RS232 serial REMOTE port.
(1) power jack.

Controls: (1) Front panel pushbutton allows local selection of switch position, A or B.

Display: (2) LED's to indicate position status and power.
Power: 12 VAC at .5 Amp, UL Approved 120 VAC, 60, Hz wall mount power supply.

Dimensions: 2.75" H x 8" W x 7.25" D.
Weight: 2.5 lbs.

Electro Standards Laboratories manufactures a complete line of data network switches and cables including fiber optic. Call and discuss your requirement with application Engineers. 401-943-1164.

MODEL 7273 FUNCTION DIAGRAM:

