

Model 7250 Single Channel DB37 A/B Switch

INTRODUCTION

The PathWay® Model 7250 Single Channel DB37 A/B Switch allows the user the capability of sharing a single port interface device connected to the “COMMON” port among two other devices connected to the “A” and “B” ports.

The unit may be quickly and conveniently switched between states “A” and “B” by depressing its front-panel pushbutton.

FEATURES:

- Allows quick connection to any one of two devices from one COMMON device.
- **Switches 36 pins of the DB37 interface (Pins 2 thru 37). Pin 1 is carried through.**
- Eliminates the need to plug and unplug cables.
- Transparent to data speed and format.
- Local control via front-panel pushbutton.
- Front panel LED's display switch position and power status.
- Retains last switch position even in the event of power loss and continues to pass data.
- Attractive anodized black box packaging provides EMI/RFI shielding.
- Custom length DB37 cables available for your switch installation.



SPECIFICATIONS:

PORT CONNECTORS: (3) DB37 female connectors on rear panel are labeled A, B and COMMON.

FRONT PANEL CONTROL: (1) Manual pushbutton allows local switching.

DISPLAY: (2) Front panel LED's display switch position and power status.

POWER: UL approved 120 VAC, 60 Hz wall mount power module supplies 12 VDC, 500mA to the unit.

DIMENSIONS: Desktop 13.5" W x 2.5" H x 7.25" D.

WEIGHT: Approximately 4.5 lbs.

Model 7250 Application

