

# PathWay® Model 7298 Three-Channel XLR A/B Switch, with Contact Control Remote Port, 1U Rackmount

- **Ideal for professional audio equipment switching.**

## INTRODUCTION

Each channel of the PathWay® Model 7298 3-Channel XLR A/B Switch allows the user the capability of accessing two separate XLR interface devices connected to ports A and B with a single XLR interface device connected to the COMMON port.

The switch may be controlled locally via the front panel pushbutton or remotely from a DB9 port located on the rear of the unit. The Remote port accepts contact closure signals. The Model 7298 dimensions are 19" W x 1.75" H x 8" D.



## FEATURES

- Each of three channels allows access to two XLR interface devices from one COMMON XLR device.
- All three channels switch simultaneously.
- Switches all three pins of the XLR interface.
- Eliminates the need to plug and unplug cables.
- Local control via front-panel pushbutton.
- Remote control port allows off-site switch management.
- Front-panel pushbutton control can be locked out, remotely.
- Front panel LED's display switch position and power status.
- Retains last switch position in the event of a power loss and continues to pass data.
- When power is restored, unit maintains last set position.
- Attractive anodized black box packaging provides EMI/RFI shielding.
- Custom length XLR cables available for your switch installation.

## SPECIFICATIONS:

**PORT CONNECTORS:** (2) XLR female connectors labeled A and B for each of the three channels. (1) XLR male connector labeled COMMON for each of the three channels.

**FRONT PANEL CONTROL:** (1) Manual pushbutton allows local switching.

**DISPLAY:** (2) Front panel LED's display switch position and power status.

**REMOTE:** (1) DB9 (F) connector on rear panel accepts Contact Closure transition signals for Remote Control operation.

**POWER:** UL approved 120VAC, 60Hz wall mount power module supplies 12 VDC, 500 mA to the unit.

**DIMENSIONS:** Rackmount configuration 19.0" W x 1.75" H x 8.0" D. (48.3 x 4.4 x 20.3 cm)

**WEIGHT:** Approximately 4.6 lbs. (2.1 Kg)

**OPTION: WIDE RANGE POWER MODULE** (Cat No 517277) CE and UL listed table mount power module, 100VAC/240VAC, 50Hz/60Hz in place of standard 115VAC or 120VAC power module. Ideal for international applications.

## Model 7298 Application

