

PathWay® Model 7299 Eight-Channel XLR A/B/C Switch, with Contact Control Remote Port, 3U Rackmount

• Ideal for professional audio equipment switching.

INTRODUCTION

Each channel of the PathWay® Model 7299 8-Channel XLR A/B/C Switch allows the user the capability of accessing three separate XLR interface devices connected to ports A, B and C with a single XLR interface device connected to the COMMON port.

The switch may be controlled locally via the front panel pushbutton or remotely from a DB9 port located on the rear of the unit. The Remote port accepts contact closure signals.

FEATURES

- Each of eight channels allows access to three XLR interface devices from one COMMON XLR device.
- All eight channels switch simultaneously.
- Switches all three pins of the XLR interface.
- Eliminates the need to plug and unplug cables.
- Local control via front-panel pushbutton.
- Remote control port allows off-site switch management.
- Front-panel pushbutton control can be locked out, remotely.
- Front panel LED's display switch position and power status.
- Retains last switch position in the event of a power loss and continues to pass data.
- When power is restored, unit maintains last set position.
- Attractive anodized black box packaging provides EMI/RFI shielding.

OPTION: WIDE RANGE POWER MODULE (Cat No 517277) CE and UL listed table mount power module, 100VAC/240VAC, 50Hz/60Hz in place of standard 115VAC or 120VAC power module. Ideal for international applications.



SPECIFICATIONS:

PORT CONNECTORS: (3) XLR female connectors labeled A, B and C for each of the eight channels. (1) XLR male connector labeled COMMON for each of the eight channels.

FRONT PANEL CONTROL: (1) Manual pushbutton allows local switching.

DISPLAY: (3) Front panel LED's display switch position and power status.

REMOTE: (1) DB9 (F) connector on rear panel accepts Contact Closure transition signals for Remote Control operation.

POWER: UL approved 120VAC, 60Hz wall mount power module supplies 12 VDC, 500 mA to the unit.

DIMENSIONS: Rackmount configuration 19.0" W x 5.25" H x 10.0" D. (48.3 x 13.3 x 25.4 cm)

WEIGHT: Approximately 8.5 lbs. (3.9 Kg)

