

PathWay® Model 7362 RJ45 10/100 Base-T A/B/C Switch, Cat 5, with Serial Remote Control

- **Provides Cat5 Performance**

INTRODUCTION

The PathWay® Model 7362 RJ45 10/100 Base-T A/B/C Switch allows the user the capability of sharing one RJ45 device connected to the COMMON port among three other devices connected to the "A", "B", and "C" ports. The switch may be controlled locally by manually operating the front panel pushbuttons or remotely from the DB9 REMOTE port located on the rear of the unit. The REMOTE port provides control through RS232 serial commands and allows the user to both control and monitor the switch position.

FEATURES:

- **Allows quick connection to any one of three RJ45 devices from one COMMON device.**
- Switches all 8 pins of the RJ45 interface.
- Eliminates the need to plug and unplug cables.
- Transparent to data speed and format.
- Rated for 10/100 Base-T networks (up to Cat5).
- Local control via front-panel pushbuttons.
- Remote control port allows off-site monitoring and switch management.
- The REMOTE port accepts RS232 Serial Data ASCII commands for switch position control and monitoring.
- Front-panel pushbutton control can be locked out, remotely.
- Front panel LED's display switch position and power status.
- Retains last switch position in the event of power loss and continues to pass data.
- Attractive anodized black box packaging provides EMI/RFI shielding.
- Custom length RJ45 cables available for your switch installation.



SPECIFICATIONS:

PORT CONNECTORS: (4) RJ45 female connectors are labeled A, B, C, and COMMON.

FRONT PANEL CONTROL: (3) Manual pushbuttons allow local switching.

DISPLAY: (3) Front panel LED's display switch position and power status.

REMOTE CONTROL: (1) DB9 female connector on rear panel accepts ASCII RS232 Serial Data for Remote Control operation.

POWER: UL approved 120VAC, 60 Hz wall mount power module supplies 12 VDC, 500mA to the unit.

DIMENSIONS: Rackmount Configuration: 19.0" W x 1.75" H x 8." D. (48.3 x 4.4 x 20.3 cm).

WEIGHT: Approximately 4.5 lbs. (2.0 Kg)

OPTION: WIDE RANGE POWER MODULE

(Cat No 517277) CE and UL listed table mount power module, 100VAC/240VAC, 50Hz/60Hz in place of standard 115VAC or 120VAC power module. Ideal for international applications.

MODEL 7362 APPLICATION:

