Electro Standards Laboratories
ADVANCED SYSTEMS DESIGN & SERVICES

Model 9093 Dual-Channel DB9 A/B/C Switch, Manual, Simultaneous Switching, Rackmount

INTRODUCTION

With each of its two channels, the Model 9093 DB9 A/B/C Switch allows the user to access three DB9 devices connected to its A, B, and C ports with one DB9 device connected to its COMMON port. The two channels are switched simultaneously via a knob located on the front panel. See the application diagram below.

Features:

- Simultaneously switches two DB9 channels via the front panel rotary switch.
- All 9 pins of the DB9 interface are switched.
- Eliminates the need to plug and unplug cables.
- Transparent to data speed and format.
- High quality sealed switch with self-wiping precious metal contacts.
- No external power required.
- Improves computer network efficiency by allowing sharing of peripherals.
- Attractive anodized black box packaging provides EMI/RFI shielding.
- Rackmount configuration, with dimensions: 19" W x 1.75" H x 8.0" D.
- Weight: 4.5 lbs (2.0 kg).
- Standard or custom length cables available for your switch installation.

SPECIFICATIONS:

PORT CONNECTORS: (3) DB9 (F) connectors labeled A, B, and C, as well as (1) DB9 (M) for Channel 1, and (3) DB9 (F) connectors labeled A, B, and C, as well as (1) DB9 (M) for Channel 2.

FRONT PANEL CONTROL: (1) Rotary selector switch allows local switching.

POWER: No power required. Manually operated.

DIMENSIONS: Rackmount 19.0" W x 1.75" H x 8.0" D.

WEIGHT: Approximately 4.5 lbs (2.0 kg).

Do you require a variation from this specification? Call to discuss!

Custom Length DB9 cables available for your switch installation. State cable length (XXX) when ordering.		
Part Number	**Description**	**Price** (USD)
990127-XXX	XXX Feet, DB9 F/F, 9-Conductor Unshielded PVC Cable	$14.50 + $0.30/ft
990125-XXX	XXX Feet, DB9 M/F, 9-Conductor Unshielded PVC Cable	$14.50 + $0.30/ft
990126-XXX	XXX Feet, DB9 M/M, 9-Conductor Unshielded PVC Cable	$14.50 + $0.30/ft

Model 9093 Application

36 Western Industrial Drive, Cranston, RI 02921
Tel: 401-943-1164   Fax:401-946-5790
www.ElectroStandards.com
E-mail:eslab@ElectroStandards.com

Pub. 4746-01