

Model 9451 DB25 A/B/C Switch, Manual, Rackmount

INTRODUCTION

The Model 9451 DB25 A/B/C Switch allows the user to access three DB25 devices connected to its A, B, and C ports with one DB25 device connected to its COMMON port. The unit is manually operated, requiring no power. Port selection is quick and easy via a front panel rotary switch.

FEATURES:

- Allows quick connection to any one of three DB25 devices from one COMMON device.
- Manual operation via front-panel rotary switch.
- High quality sealed switch with self-wiping low impedance contacts.
- Transparent to data speed and format.
- All 25 pins of the DB25 interface are switched.
- Eliminates the need to plug and unplug cables.
- No external power required.
- Attractive anodized black box packaging provides EMI/RFI shielding.
- Custom length DB25 cables available for your switch installation.
- Lifetime guarantee against manufacturing defects.



SPECIFICATIONS:

PORT CONNECTORS: (4) DB25 female connectors labeled A, B, C and COMMON.

FRONT PANEL CONTROL: (1) Rotary switch on front panel selects A, B, C.

POWER: No power required. Manually operated.

DIMENSIONS: Rackmount 19.0" W x 1.75" H x 8.0" D.
(48.3 x 4.4 x 20.3 cm)

WEIGHT: Approximately 2.0 lbs. (0.9 Kg)

**Do you require a variation
from this specification?
Call to discuss!**

Custom length data network cables 25-conductor, DB25/DB25, Unshielded, PVC.

Part Number	Connectors	Length Specify XXX-FT	Price (USD)
990104-XXX	F/F	XXX-FT	\$19.00 + 0.55 / FT
990105-XXX	M/F	XXX-FT	\$19.00 + 0.55 / FT
990106-XXX	M/M	XXX-FT	\$19.00 + 0.55 / FT

