

Supplied to
Telco
Field Technicians
Worldwide!

Telephone / Telecom Test Kit

- Kit contains thirteen high quality cables designed to facilitate test and access of high speed data interfaces.
- Designed with input from telco network installers and telco linesmen.

Electro Standards Laboratories manufactures a complete selection of telephone/telecom patch cables that are compatible with all standard telephone systems, data and voice test equipment, and patch/interconnect devices. All of the cables are of the highest quality, manufactured in U.S.A. Custom designed cables utilizing these standard connectors are also available.

- Test Kit contains thirteen cables designed to facilitate test and access of high speed data interfaces.
- All cables are packaged in a handy Test Kit Carry Case for maximum protection.
- Includes an information manual delineating each cable configuration.
- Custom-design cables and Custom-content kits available to suit your specific needs.



The #930849 TEST KIT contains:

Qty.	Catalog No.	Length	Description
2	930840-006	6 Ft.	Cables: Bantam Plug/Bantam Plug
2	930841-006	6 Ft.	Cables: Bantam Plug/Two Telco Piercing Alligator Clips
3	930842-006	6 Ft.	Cables: WE310 Plug/Bantam Plug
3	930843-005	5 Ft.	Cables: WE310 Plug/Two Telco Piercing Alligator Clips
1	930844-006	6 Ft.	Cable: DB-15 Female/Two Bantam Plugs, T-1
1	930845-006	6 Ft.	Cable: DB-15 Male/Two Bantam Plugs, T-1
1	930847-006	6 Ft.	Cable: RJ-48 Plug/Two Bantam Plugs
1	930848	-- --	Test Kit Carry Case

BANTAM PLUG/BANTAM PLUG


Two miniature 3-conductor **nickel phone plugs**, connected by shielded paired cable having a **high-flex PVC** jacket. The standard length is 6 feet. Custom lengths available on request.



Cat#930840-006 Length 6 Ft.

BANTAM PLUG/TWO TELCO PIERCING ALLIGATOR CLIPS

A miniature 3-conductor **nickel phone plug** connected to two piercing alligator clips having one red and one black vinyl boot. The cable is 26 AWG, shielded, twisted pair with **high-flex PVC** jacket.



Cat#930841-006 Length 6 Ft.

more →

WE310 PLUG/BANTAM PLUG

A PJ-051 nickel phone plug and a miniature 3-conductor **nickel phone plug** connected by shielded paired cable having a **high-flex PVC** jacket. Standard lengths are 3 feet, 5 feet, and 6 feet.



Cat#930842-006 Length 6 Ft.

WE310 PLUG/TWO TELCO PIERCING ALLIGATOR CLIPS

A PJ-051 **nickel phone plug** connected to two piercing alligator clips having one red and one black vinyl boot. The cable is 26 AWG, shielded, twisted pair with **high-flex PVC** jacket. Standard lengths are 5 feet and 10 feet.



Cat#930843-005 Length 5 Ft.

DB-15 FEMALE/TWO BANTAM PLUGS, T-1


A DB-15 female connector, metal hood with thumbscrews, connected to two miniature 3-conductor **nickel phone plugs**. The cable is 26 AWG, shielded, twisted pair with **high-flex PVC** jacket. Paired: Pins 1 & 9 to TX Tip & Ring, pins 3 & 11 to RX Tip & Ring. Standard length is 6 feet. The TX plug is RED, the RX plug is BLACK.



Cat#930844-006 Length 6 Ft.

DB-15 MALE/TWO BANTAM PLUGS, T-1


A DB-15 male connector, metal hood with thumbscrews, connected to two miniature 3-conductor **nickel phone plugs**. The cable is 26 AWG, shielded, twisted pair with **high-flex PVC** jacket. Paired: Pins 1 & 9 to TX Tip & Ring, pins 3 & 11 to RX Tip & Ring. The TX phone plug is Red, the RX phone plug is BLACK.



Cat#930845-006 Length 6 Ft.

RJ-48 PLUG/TWO BANTAM PLUGS

An RJ-48 plug with molded grip connected to two miniature 3-conductor **nickel phone plugs**. The cable is 26 AWG, shielded twisted pair with **high-flex PVC** jacket. Paired: Pins 5 & 4 to TX Tip & Ring, pins 2 & 1 to RX Tip & Ring. Standard length is 6 feet. The TX plug is RED, the RX plug is black.



Cat#930847-006 Length 6 Ft.

TEST KIT CARRY CASE

A convenient carry case for the test leads. Size: 8 x 11 x 3 inches. Provides protection for the cables and connectors. Zippered. A separator and an outside pocket provides compartments for manuals.



Cat#930848 Carry Case

CUSTOM CABLE LENGTHS AVAILABLE

The cable lengths indicated are the Test Kit standards. However, any of the cables may be ordered, individually, and at custom lengths. To order a custom length cable, use the same 6-digit portion of the catalog number and change the three-digit portion to indicate the length in feet. Example: The 930840-006 cable is 6 feet long, as a standard. It may be ordered as a 20-foot cable by specifying as follows: 930840-020.

OPTIONALLY AVAILABLE CABLE

DB-15 MALE/DB-15 MALE, T-1

A DB-15 male to male cable, T-1 pairing: Pins 1 & 9 and 3 & 11, straight thru. The cable is 26 AWG, shielded, twisted pair with **high-flex PVC** jacket. Standard length is 6 feet. The connectors have metal hoods and long thumbscrews.



Cat#930846-006 Length 6 Ft.