

VersaLink Plastic Optical Fiber (POF) Patch Cord

• Ideal for Casino / Gaming VLT Network Applications

SIMPLEX, NON-LATCHING

VersaLink Plastic Optical Fiber Patch Cords feature the Versatile Link (“VersaLink”) connectors providing ready made solutions for rapid installations for any industrial or commercial application utilizing the Avago Technologies Versatile Link transceivers. Cables are available in standard and custom lengths. Although this specification refers to simplex non-latching patch cords, Versalink cables can be simplex or duplex cable featuring either latching or non-latching connectors.

The simplex cables are constructed with a single step-index plastic optical fiber sheathed in a black polyethylene jacket.

The duplex cables are constructed with two step-index plastic optical fibers sheathed in a black polyethylene jacket.



Features:

- All patch cord is manufactured with 1mm diameter plastic optical fiber.
- Compatible with Avago Versatile Link family of connectors and fiber optic components.
- Direct replacement for Avago part number HFBR-EU550.
- Simplex, non-latching connector.
- UL-rated fiber cable and connections.
- Connector terminations are crimped and epoxied for maximum retention.
- Terminations are polished to a 1µm finish to ensure high coupling efficiency.
- Standard and custom lengths available.

Applications:

- Industrial data links for factory automation and plant control.
- IntraSystem links (board-to-board, rack-to-rack)
- Telecommunications switching systems
- Computer-to-peripheral data links (PC bus extension)
- Proprietary LANs
- Digitized video
- Medical instruments
- High voltage isolation
- Gaming Terminal Networks

- For use with ESL Fiber/RS485 Converters, (Model 4127, 4129)
- For use with ESL Fiber/RS232 Converters. (Model 4137, 4139)



Simplex, Non-Latching



Fiber/485



Fiber/232

Mechanical/Optical Characteristics, -40 to +85°C				
Parameter	Min	Typ	Max	Unit
Cable Attenuation	0.15	0.22	0.27	db/m
Diameter, Core & Cladding	0.94	1.00	1.06	mm
Diameter, Jacket	2.13	2.20	2.27	mm
Propagation Delay Constant	–	5.0	–	ns/m
Cable Length Tolerance	-0	0	+3	in.

Catalog No.	Cable Length
986625-010	10 Feet
986625-020	20 Feet
986625-030	30 Feet
986625-040	40 Feet
986625-XXX	XXX Feet (Specify)