

IP60-200 INTENSIFIER PUMP

**HIGH VELOCITY STREAM OF
ULTRA HIGH PRESSURE WATER**



The IP60-200 is a waterjet pump beast. With a 4.0 gpm flow rate at 55,000 psi dynamic, you can run up to four 15/45 orifice/ nozzle combinations to cut through thick material and generate four parts at a time. You'll be able to cut your application's material and time spent on the job with this versatile pump.

IP60-200 AT A GLANCE

- Rated pressure: 60,000 psi (4,100 bar)
- UHP flow rate: 4.0 gpm (15.2 lpm)
- Max rated orifice size .28 in (.71 mm)
- Single piston, dual plunger, reciprocating pump
- Motor output: 200 hp (149 kw)

CONSTRUCTION

- Heavy gauge sheet metal covers
- Rugged all steel welded framework
- Hinged cover & quick remove access covers

CONTROLS

- UL Certified electrical panel
- Safety shutdown systems
- Automatic safety pressure bleed-down valve
- Optional advanced control package

INTENSIFIER PUMP

- Double, 2 quarts (1.9 liters) attenuator
- Single piston, dual plunger, reciprocating pump
- Rated Pressure: 60,000 psi (4100 bar)
- UHP flow rate: 4.0 gpm (15.2 lpm)
- Max rated orifice size .28 in (.71 mm)

ELECTRIC MOTOR

- Motor output: 200 hp (149 kw)
- TEFC NEMA premium efficiency motor
- Full load amps @ 460vac: (60Hz) 240
- Full load amps @ 230vac: (60Hz) 480
- Full load amps @ 380vac: (50Hz) 288

SIZE

- Length: 95 in (2420 mm)
- Width: 60 in (1530 mm)
- Height: 60 in (1530 mm)
- Approximate weight with fluid: 6,200 lbs. (2812 kg)

HYDRAULICS

- Axial piston, variable displacement, pressure-compensated hydraulic pump
- Thermostatically-controlled cooling loop
- Hydraulic accumulator prolongs component life and improves output quality
- Reservoir capacity: 104 gallons (394 liters)

WATER/ENVIRONMENT

- Low-pressure water supply requirement 3.3 gpm (12.5 lpm) @ 60 psi (4.1 bar) min.
- Max temp 70°F (21°C)
- Ambient temperature: 50-100°F (10-37° C)

WARRANTY

- 1-year or 2,000-hour pump warranty
- 2-year or 4,000 hour hydraulic circuit warranty
- Lifetime factory product training



THE HEART OF YOUR COMPANY

GIVE YOUR APPLICATION THE TOUGH LOVE IT DESERVES

PUMPS	PRESSURE RATING	ELECTRIC MOTOR	INTENSIFIER	HYDRAULICS	OUTPUT	DIMENSIONS
IP60-30	60,000 psi (4,100 bar)	30 hp (22 kw)	Single 1 quart (0.9 liters) attenuator	30 gal (113 liters) Thermostatically cooled	UHP flow rate: 0.6 gpm (2.3 lpm) Max orifice: .010 in (.25 mm)	Length: 72 in Width: 32 in Height: 53 in
IP60-50	60,000 psi (4,100 bar)	50 hp (37 kw)	Single 1 quart (0.9 liters) attenuator	35 gal (135 liters) Thermostatically cooled	UHP flow rate: 1.0 gpm (3.7 lpm) Max orifice: .015 in (.38 mm)	Length: 74 in Width: 37 in Height: 53 in
IP60-75	60,000 psi (4,100 bar)	75 hp (56 kw)	Single 1 quart (0.9 liters) attenuator	55 gal (209 liters) Thermostatically cooled	UHP flow rate: 1.5 gpm (5.7 lpm) Max orifice: .018 in (.46 mm)	Length: 86 in Width: 40 in Height: 55 in
IP60-100	60,000 psi (4,100 bar)	100 hp (75 kw)	Double 2 quarts (1.9 liters) attenuator	54 gal (204 liters) Thermostatically cooled	UHP flow rate: 2.0 gpm (7.6 lpm) Max orifice: .021 in (.53 mm)	Length: 83 in Width: 40 in Height: 56 in
IP60-150	60,000 psi (4,100 bar)	150 hp (112 kw)	Double 2 quarts (1.9 liters) attenuator	103 gal (390 liters) Thermostatically cooled	UHP flow rate: 3.0 gpm (11.4 lpm) Max orifice: .025 in (.64 mm)	Length: 83 in Width: 56 in Height: 56 in
IP60-200	60,000 psi (4,100 bar)	200 hp (149 kw)	Double 2 quarts (1.9 liters) attenuator	104 gal (394 liters) Thermostatically cooled	UHP flow rate: 4.0 gpm (15.2 lpm) Max orifice: .28 in (.71 mm)	Length: 95 in Width: 60 in Height: 60 in
XP90-50	90,000 psi (6,200 bar)	50 hp (37 kw)	Single 2 quarts (1.9 liters) attenuator	36 gal (136 liters) Thermostatically cooled	UHP flow rate: 0.7 gpm (2.61 lpm) Max orifice: .011 in (.28 mm)	Length: 72 in Width: 32 in Height: 53 in
XP90-100	90,000 psi (6,200 bar)	100 hp (75 kw)	Double 2 quarts (1.9 liters) attenuator	55 gal (208 liters) Thermostatically cooled	UHP flow rate: 1.45 gpm (5.51 lpm) Max orifice: .017 in (.43 mm)	Length: 86 in Width: 40 in Height: 55 in

READY TO BUILD YOUR MACHINE?

Contact a Jet Edge sales partner for your FREE engineering analysis. Whether you're cutting with water only or running a 24/7 operation with multiple abrasive jets, we can find the perfect pump for your application—even if that means a custom creation.