

# IP60-1005 INTENSIFIER PUMP

# SINGLE INTENSIFER

#### Construction

- · Heavy gauge sheet metal covers
- · Rugged all-steel welded framework
- · Hinged cover and removable access panels for convenient machine inspection and maintenance
- · Integral hydraulic reservoir
- · Optional Sound Insulation Package
- · NEMA 12/13 rated electrical enclosure

#### **Standard Features**

- · High efficiency TEFC motor
- · 1,500 or 1,800 nominal motor speed (rpm)
- · Wye-Delta soft start with disconnect
- · Programmable Logic Controller (PLC) for operation and diagnostics
- · Electronically shifted intensifiers
- · Safety shutdown systems
- · Automatic safety pressure bleed-down valve
- · Axial piston, variable displacement, pressure-compensated hydraulic pump
- · Thermostatically controlled cooling system
- · 0.5 gallon (1.9 liter) high pressure attenuator
- · In-line UHP Water Filter to 5 Micron
- · UHP safety shielded tubing
- · Liquid-filled pressure gauges

# **Physical Size**

- · Length: 86 in (218 cm)
- · Width: 40 in (102 cm)
- · Height: 55 in (140 cm)
- · Approximate Weight with Fluid: 4,600 lbs. (2087 kg)

# **Electric Motor**

- · Motor Output: 100 hp (75 kw)
- · Motor Type: High Efficiency TEFC electric motor
- · Full load amps @ 460vac: (60Hz) 119
- · Full load amps @ 230vac: (60Hz) 238
- · Full load amps @ 380vac: (50Hz) 147

# Intensifier

- · Type: Single piston, dual plunger, reciprocating
- · Number of Intensifiers: 1
- · Rated Pressure: 60,000 psi (4,100 bar)
- · Intensification Ratio: 19:1
- · Flow Rate: 2.0 gpm (7.6 lpm)
- · Maximum Rated Orifice Size: .021 in (0.53 mm)



## **Low-Pressure Water/Intensification Water**

- · Type: Pretreated, <100 TDS, PH 6-8, Silica <15PPM
- · Supply Requirements: 4.0 gpm @ 20 psi (1.4 bar) min. / 75°F (24°C) max
- · Filtration: 10, 1, .45 Micron

#### **Coolant Water**

- · Maximum Temperature: 70°F (21°C)
- · Minimum: 10.0 gpm (0-37.9 lpm) @ Minimum 30 psi (2.1 bar)
- · Ability to Remove: 97,000 BTU's / Hour
- · Heat Exchanger: Braised Plate

## **Hydraulics**

- · Reservoir Capacity: 60 gallons (230 liters)
- · Filtration: 10 Micron
- · Bladder type accumulators

#### **Environmental**

- · Ambient Room Temperature: 50°-100°F (10°-37°C)
- · Relative Humidity: Noncondensing, Maximum 95% @ 100°F



Specifications subject to change.

www.jetedge.com