

XP90-50 INTENSIFIER PUMP

Construction

- · Heavy gauge sheet metal covers
- · Rugged all-steel welded framework
- · Hinged cover and removable access panels for convenient machine inspection and maintenance
- · Integral hydraulic reservoir
- · Sound insulated for quiet operation
- · NEMA 12/13 rated electrical enclosure

Standard Features

- · High efficiency TEFC motor
- · Electronically shifted intensifiers
- · Wye-Delta soft start with disconnect
- · 0.5 gallon (1.9 liter) high pressure attenuator with filtration to .45 micron
- · Safety shutdown systems
- · Automatic safety pressure bleed-down valve
- · Thermostatically controlled cooling system
- · Dual pressure set points
- · Programmable Logic Controller (PLC) for operation and safety monitoring
- · Axial piston, variable displacement, pressure-compensated hydraulic pump
- · Liquid filled pressure gauges
- · UHP safety shielded tubing

Physical Size

- · Length: 72 in (1,830 mm)
- · Width: 32 in (820 mm)
- · Height: 53 in (1, 350 mm)
- · Approximate Weight with Fluid: 2,700 lbs. (1,230 kg)

Electric Motor

- · Motor Output: 50 hp (37 kw)
- · Motor Type: High Efficiency TEFC electric motor
- · Full load amps @ 460vac (60Hz): 58
- · Full load amps @ 230vac (60Hz): 116
- · Full load amps @ 380vac (50Hz): 71

Intensifier

- · Type: Single piston, dual plunger, reciprocating
- · Number of Intensifiers: one
- · Rated Pressure: 90,000 static psi (6,200 bar)
- · Intensification Ratio: 25:1
- · Flow Rate: 0.7 gpm (2.61 lpm)
- · Maximum Rated Orifice Size .011 in (.28mm)
- · 100,000 PSI-rated fittings and tubing
- · Supports 75K+ continuous operating pressure



Low-Pressure Water/Intensification Water

- · Type: Pretreated, <100 TDS, PH 6-8, Silica <15PPM
- · Supply Requirements: 2.0 gpm @ 40 psi (3 bar) min. / 70°F (21°C) max.
- · Filtration: 1, .45 Micron

Coolant Water

- · Maximum Temperature: 70°F (21°C)
- · Minimum: 2.5 gpm (9.5 lpm) @ Minimum 20 psi (1.3 bar)
- · Ability to Remove: 39,000 BTUs /Hour

Hydraulics

- · Reservoir Capacity: 45 gallons (170 liters)
- · Filtration: Full Flow 10 Micron

Environmental

- · Ambient Room Temperature: 50°-95°F (10°-35°C)
- · Relative Humidity: Non-condensing, Maximum 95% @ 100°F



Specifications subject to change.



www.jetedge.com

+1-763-497-8700 | 1-800-JET-EDGE sales@jetedge.com